

SLURRY TANKER



SMST-15



SMST-15



SMST-10



SMST-5



GENERAL FEATURES

Slurry tankers are designed to suck slurry from the lagoons and homogeneously spread on fields. Special low height design, floatation tyres and strong chassis are some of the features of slurry tankers. These features allow users to operate on all kind of terrain, store the machine inside low height buildings and maintain the machine easily. Slurry tankers have strong Italian pumps that allow users to operate faster and spread on a wider area. There are indicators to follow pressure and slurry level, over pressure and low pressure valves and overfilling protection on the machine. With these indicators and safety systems, operators are able to work with full control without damaging the machine.

TECHNICAL DETAILS

CODE	TYPE OF AXLE	CAPACITY (TON)	PUMP TYPE	TYRE	PTO ROTATION (RPM)	DISTRIBUTOR TYPE
SMST-5	SINGLE AXLE	5	OIL PALLET	500x50x17	540	HITTING THE PLATE
SMST-10	DOUBLE AXLE	10	OIL PALLET	500x50x17	540	HITTING THE PLATE
SMST-15	DOUBLE AXLE	15	OIL PALLET	500x50x17	540	HITTING THE PLATE
SMST-20	DOUBLE AXLE	20	OIL PALLET	600X50X22,5	540	HITTING THE PLATE





SOIL MASTER
AGRICULTURAL MACHINERY

HEAD OFFICE

Add: Fevzi Cakmak Mh. 10758 Sk. No: 16/G
42050 Karatay/Konya/TURKEY

T: +90 332 290 00 20
F: +90 332 290 00 19

FACTORY

Add: Büyükkayacık Osb, Yaylacık Cd. No:
23, 42250 Selcuklu/Konya/TURKEY

T: +90 332 239 18 85
T: +90 332 239 18 86
F: +90 332 239 18 87

www.soilmaster.com.tr



+90 (532) 137 01 74



info@soilmaster.com.tr



SOILMASTER AGRICULTURAL MACHINERY



For detailed information about
our products, you can scan the
QR code by your device.